Data Sheet

Coaxial Panel Connector 23_N-50-0-1/133_N

Description

Straight panel receptacle jack, flange mount

Interface standards IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data		
Impedance	50 Ω	
Interface frequency max.	11 GHz	
Mechanical Data		
Number of matings	500	
Weight	0.0301 kg	
Environmental Data		
Operating temperature	-65 °C to 165 °C	
2011/65/EU (RoHS)	compliant	
Material Data		
Piece Parts	Material	Surface Plating
Centre contact	Bronze	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Related Documents		
Outline drawing	DOU-00010382	
Outline drawing Catalogue drawing	DOU-00010382 DCA-00010384	

Ordering Information

Single package

23_N-50-0-1/133_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

