# **Data Sheet**



# Coaxial Panel Connector 22\_QLA-01-0-1/112\_N

#### **Description**

Straight bulkhead receptacle jack

Interface standards
NIM-CAMAC-Standard CD/N549



#### **Technical Data**

**Electrical Data** 

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 1.4 \ \text{GHz} \end{array}$ 

**Mechanical Data** 

Number of matings 10000 Weight 0.0028 kg

**Environmental Data** 

Operating temperature -55 °C to 150 °C 2011/65/EU (RoHS) compliant

## **Material Data**

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Bronze	Gold Plating (Nickel underplated)
Body	Brass	Nickel Plating
Insulator	PFA / PTFE	
Fastening nut	Brass	Nickel Plating
Washer	Bronze	Nickel Plating

#### **Related Documents**

Catalogue drawing DCA-00010163

Mounting hole DOU-00009337

## **Ordering Information**

 Single package
 22\_QLA-01-0-1/112\_NE

 Bulk 100 pcs package
 22\_QLA-01-0-1/112\_NH

#### **Remarks**

For fastening nut, face spanner 74\_Z-0-0-25 is recommended

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.