Data Sheet



Coaxial PCB Connector 92_MMBX-S50-0-12/111_N

Description

Edge mount PCB jack

Interface Standards
SUHNER-MMBX



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 12.4 \ \text{GHz} \end{array}$

Mechanical Data

Board mounting type edge mount Weight 0.0011 kg

Environmental Data

Operating temperature $$-55\ ^{\circ}\text{C}$$ to 155 $^{\circ}\text{C}$$ 2011/65/EU (RoHS) compliant

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------------------------|-----------------|
| Centre contact | Brass | SUCOPRO Plating |
| Outer contact | Brass | SUCOPRO Plating |
| Body | Brass | SUCOPRO Plating |
| Insulator | LCP (Liquid crystal polymer) | |

Related Documents

Outline drawing DOU-00013388
Catalogue drawing DCA-00013390
Mounting hole DOU-00013391

Ordering Information

 Tape and Reel package
 92_MMBX-S50-0-12/111_NM

 Single package
 92_MMBX-S50-0-12/111_NE

Remarks

PCB connector without stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.